

AP362e with ADR SOL I N G printer

SEMI-AUTOMATIC BOTTLE LABELER WITH INTEGRATED PRINTER



FEATURES:

- Processes up to 1200 products/hour.
- Printing width of 1 inch (12.7 mm).
- Capable of applying up to two labels
- Built-in label counter
- Compact machine dimensions
- Various inks available for both porous and non-porous surfaces
- Printing speed of up to 100m/minute
- Automatic Ink Management
- Also available as an upgrade for previously purchased AP362e models

The AP362, featuring the integrated ADR SOL I N G Printer, is a versatile solution for precise labeling and printing of cylindrical containers like bottles. Combining a state-of-the-art semi-automatic labeler and powerful TIJ Printer, it delivers industry-grade quality in compact form. With a processing capacity of up to 1200 bottles per hour, based on the proven AP362e, it ensures impressive precision and speed. The advanced technology of the ADR SOL I N G Printer supports various inks for printing on diverse surfaces, from porous materials like paper labels and cardboard to smooth ones like plastic, glass, and even stainless steel. Equipped with an intuitive color display and touchscreen interface, the printer offers ease of operation in 13 pre-installed languages, simplifying both operation and training. Whether you're a novice or seasoned professional, rely on this system for efficient and precise performance.

AP362e with ADR SOL I NG printer

SPECIFICATIONS

| | |
|------------------------|---|
| Model | AP362e with ADR SOL I NG printer |
| Technology | HP TIJ 2.5 Thermal Inkjet Technology |
| Resolution | Vertical: 600dpi; Horizontal 40 - 1200dpi |
| Printing Width | 12,7mm (1") |
| Printing speed | Up to 100m/min (Fast dry cartridges) |
| Application speed | 101mm/s or up to 1200 containers in one hour |
| Container sizes (HxW) | 15 - 170 mm (0,6 - 6,7") x 25,4 - 238 mm (1 - 9,4") |
| Label sizes (HxW) | 19,1 - 609,6 mm (0,75 - 24") x 19,1 - 209 mm (0,75 - 8,25") |
| Label type | Die cut with waste removed. Clear labels can be used. |
| Gap between the labels | Recommended: 3,175 - 6,3500 mm (1/8 - 1/4") |
| Weight | 11,5 Kg |
| Dimensions (HxWxD) | 520 mm x 460 mm x 325 mm |
| Power Requirements | 100-240V AC (50/60 Hz), 12 V DC, 5.0 A |
| Certificates | FCC, CE, RoHS |



Ask for an upgrade!

The ADR SOL I NG Printer is also offered as an upgrade option for those who have already acquired the AP362e. If you're considering an upgrade, feel free to reach out to us. We'll thoroughly evaluate the feasibility of the conversion and provide you with a tailored offer.